



Get Started with Intel® MPI Library

for Intel® oneAPI on Linux* OS

The Intel® MPI Library is a multi-fabric message passing library that implements the Message Passing Interface, version 3.1 (MPI-3.1) specification. Use the library to develop applications that can run on multiple cluster interconnects.

Intel MPI Library has the following features:

- Scalability up to 340k processes
- Low overhead enables analysis of large amounts of data
- MPI tuning utility for accelerating your applications
- Interconnect independence and flexible runtime fabric selection

Intel MPI Library is available as a standalone product, as part of the [Intel® Parallel Studio XE Cluster Edition](#), and as part of the Intel® oneAPI HPC Toolkit.

Product Contents

The product consists of the following main components:

- Compilation tools, including compiler drivers such as `mpiicc` and `mpifort`
- Include files and modules
- Shared (`.so`) and static (`.a`) libraries, debug libraries, and interface libraries
- Process Manager and tools to run programs
- Test code
- Documentation provided as a separate package or available from the Intel Developer Zone

Intel MPI Library also includes [Intel® MPI Benchmarks](#), which enable you to measure MPI operations on various cluster architectures and MPI implementations. For details, see the [Intel MPI Benchmarks User Guide](#). Source code is available in the [GitHub repository](#).

Key Features

Intel MPI Library has the following major features:

- MPI-1, MPI-2.2 and MPI-3.1 specification conformance
- Interconnect independence
- C, C++, Fortran* 77, Fortran 90, and Fortran 2008 language bindings

Prerequisites

Before you start using Intel MPI Library, make sure to complete the following steps:

1. Source the `vars.sh` script to establish the proper environment settings for the Intel MPI Library. The script is located at `<install-dir>/mpi/<version>.<update>/env`, where `<install-dir>` is the Intel oneAPI HPC Toolkit installation directory (by default, `/opt/intel/oneapi`).
2. Create a `hostfile` text file that lists the nodes in the cluster using one host name per line. For example:

```
clusternode1
clusternode2
```
3. Make sure the passwordless SSH connection is established among all nodes of the cluster. It ensures the proper communication of MPI processes among the nodes.

After completing these steps, you are ready to use Intel MPI Library.

For detailed system requirements, see the “System Requirements” section in Release Notes.

Building and Running MPI Programs

Compiling an MPI Program

1. Make sure you have a compiler in your `PATH`. To check this, run the `which` command on the desired compiler. For example:

```
$ which icc
/opt/intel/inteloneapi/compiler/<version>.<update>/linux/bin/intel64/icc
```

2. Compile a test program using the appropriate compiler driver. For example:

```
$ mpiicc -o myprog <install-dir>/test/test.c
```

Running an MPI Program

Use the previously created `hostfile` and run your program with the `mpirun` command as follows:

```
$ mpirun -n <# of processes> -ppn <# of processes per node> -f ./hostfile ./myprog
```

For example:

```
$ mpirun -n 2 -ppn 1 -f ./hostfile ./myprog
```

The test program above produces output in the following format:

```
Hello world: rank 0 of 2 running on clusternode1
```

```
Hello world: rank 1 of 2 running on clusternode2
```

This output indicates that you properly configured your environment and Intel MPI Library successfully ran the test MPI program on the cluster.

Troubleshooting

If you encounter problems when using Intel MPI Library, go through the following general procedures to troubleshoot them:

- Check system requirements, known issues and limitations in the [Release Notes](#).
- Check hosts accessibility. Run a simple non-MPI application (for example, `hostname` utility) on the problem hosts with `mpirun`. This check helps you reveal the environmental problem (for example, SSH is not configured properly), or connectivity problem (for example, unreachable hosts).
- Run the MPI application with debug information enabled. To enable the debug information, set the environment variable `I_MPI_DEBUG=6`. You can also set a different debug level to get more detailed information. This action helps you find out the problem component.

See more details in the “Troubleshooting” section of the Developer Guide.

Training and Documentation

- [Online Training](#): An excellent resource for learning the Intel MPI Library capabilities through various guides, videos, webinars, and more.
- [Release Notes](#): Up-to-date information about the product, including: what's new, key features, system requirements, and known limitations.
- [Online Documentation](#): Links to all available Intel MPI Library documents.

Notices and Disclaimers

Intel technologies may require enabled hardware, software or service activation.

No product or component can be absolutely secure.

Your costs and results may vary.

© Intel Corporation. Intel, the Intel logo, and other Intel marks are trademarks of Intel Corporation or its subsidiaries. Other names and brands may be claimed as the property of others.

Intel's compilers may or may not optimize to the same degree for non-Intel microprocessors for optimizations that are not unique to Intel microprocessors. These optimizations include SSE2, SSE3, and SSSE3 instruction sets and other optimizations. Intel does not guarantee the availability, functionality, or effectiveness of any optimization on microprocessors not manufactured by Intel. Microprocessor-dependent optimizations in this product are intended for use with Intel microprocessors. Certain optimizations not specific to Intel microarchitecture are reserved for Intel microprocessors. Please refer to the applicable product User and Reference Guides for more information regarding the specific instruction sets covered by this notice.

No license (express or implied, by estoppel or otherwise) to any intellectual property rights is granted by this document.

The products described may contain design defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request.

Intel disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade.